



## Pinja Flex 30

### DESCRIPTION

A one-component water-borne acrylate paint.

### PRODUCT FEATURES AND RECOMMENDED USES

- A fast drying and flexible paint
- Suitable for wooden window frames and front doors

### TECHNICAL DATA

#### Volume solids

44%

#### Weight solids

0,53

#### Specific gravity

1,2 kg/l

#### Recommended spreading amounts and theoretical coverage

Practical coverage depends on the application method, conditions and the shape and roughness of the surface to be treated.

#### Application method

airless spraying, air assisted airless spraying

#### Gloss

Semi-matt.



# Pinja Flex 30

## APPLICATION INSTRUCTIONS

<b>Application</b>	Stir the paint carefully before use. Avoid flotation. For spray application thin the paint 5 - 15 % with water.
<b>Thinners</b>	Water
<b>VOC</b>	According to VOC Directive 2004/42/EU the product subcategory A/d VOC limit (1.1.2010) is maximum 130 g/l. VOC content of the "Pinja Flex 30" is 50±10 g/l.

**HEALTH AND SAFETY** Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets.  
A health and safety data sheet is available on request from Tikkurila Oyj.

### **For industrial and professional use only.**

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

The product is intended for professional use only and shall only be used by professionals who have sufficient knowledge and expertise on the proper use of the product. The information above is advisory only. To the extent permitted by applicable law, we shall not approve of any liability for the conditions under which the product is being used or for the use or application of the product.

In case you intend to use the product for any other purpose than that recommended in this document without first getting our written confirmation on the suitability for the intended use, such use takes place at your own risk.